CHRYSO®Aquabeton L10

Anti-water logging admixture

Chryso Concrete Solutions

DESCRIPTION

CHRYSO®Aquabeton L10 is a new generation liquid anti-washout admixture designed for the underwater placement of concrete and grout.

BENEFITS

- CHRYSO®Aquabeton L10 allows for superior resistance to washout of cementitious materials and fine aggregates, while impeding the blending of external water into the plastic concrete.
- Concrete manufactured with CHRYSO[®]Aquabeton L10 exhibit superior cohesiveness properties while remaining easy to pump and place.
- CHRYSO[®]Aquabeton L10 is compatible with most CHRYSO water reducers.

FIELDS OF APPLICATION

- Underwater concreting
- All cement types
- Marine construction
- Bridge piers
- Underwater stone blockage
- Precast products for structure and façade purpose in smooth concrete

CHARACTERISTICS

SPECIFICATIONS

Product Nature	liquid
Color	Yellow-white
Lifetime	12 months
Specific gravity	1,000 ± 0,020
рН	10,00 ± 2,00

METHOD OF USE

- Ready-to-use liquid admixture.
- The optimum dosage of CHRYSO®Aquabeton L10 can only be established after trial tests, taking into account local conditions, materials and specification requirements.
- CHRYSO®Aquabeton L10 can be added to the water before mixing the concrete. However, it can be added to the concrete after mixing but it is necessary to mix at high speed 1 min per m3 of concrete (with a minimum of 6 minutes).
- Because local job conditions vary, please contact your local CHRYSO sales representative for further assistance if using outside recommended dosage ranges.

Dosage :

0.6 to 3.00 kg per 100kg of cementitious materials 0.3 to 2.0 kg for 100 kg of cement.

PRECAUTIONS

- Protect from frost.
- Use at a temperature above 0° C.
- Should the product freeze, it will recover its properties. After thawing, an efficient agitation is necessary until the product is entirely homogeneous again.

In the event the product is exposed to temperatures below 10°C (50°F), a specific dosing equipment may be required. Please contact CHRYSO for further information regarding adapted dispensing equipments.



Prior to any use, please read carefully the Material Safety Data Sheets.

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be conducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs. www.chryso.ph

CHRYSO PHILIPPINES INC. 17 Main Ave. Severina Industrial Estate, ACSIE Comp. Km 16, West Service Rd. 1700 Paranaque City. Tél.: (+632) 823-1568 Fax.(+632) 823-6492